



SIGN PLATE & POST CONNECTION LAYOUT

## STANDARD SIGN WIDTHS


SINGLE DOUBLE 9" 12 1/8" 9" 23 1/4" 9" 34 1/8"



NAME PLATE SIGN



TELESPAR DEVICE - PLAN VIEW



[ College

UPPER SIGN

1. APPLY GREASE TO ALL SET SCREWS PRIOR TO INSTALLATION.

STREET NAME POST

- 2. APPLY DATE STICKER ON THE LOWER RIGHT HAND CORNER OF THE BACK SIDE OF THE NAME PLATE SIGNS. CITY WILL PROVIDE STICKERS.
- 3. SIGNS SHALL BE PLACED IN THE NORTHWEST CORNER AND SOUTHEAST CORNER OF THE INTERSECTION.

18" TELESPAR DEVICE

5/16" HOLE

9'

Αv

- 4. ALL STREET NAME PLATES SHALL BE 9" HIGH WITH 6" UPPER CASE AND 4.5" LOWER CASE D SERIES LETTERS AND SHALL BE 0.08 ALUMINUM E 450 PUNCH WHITE ON GREEN. SHEETING SHALL HAVE A RADIUS OF 1.5".
- 5. ALL SIGNS SHALL HAVE DIAMOND GRADE DG3 REFLECTIVE SHEETING.
- 6. THE FOLLOWING WORDS SHALL BE ABBREVIATED AS SHOWN: STREET = St , AVENUE = Av , DRIVE = Dr , LANE = Ln , COURT = Ct , ROAD = Rd

## STREET NAME PLATE SIGNS IN CONCRETE OR BITUMINOUS SURFACE NOT TO SCALE SAINT PETER STANDARD

**PLATE 8005** 

## STREET NAME PLATE SIGN IN **BITUMINOUS SURFACE** CONCRETE OR

STANDARD DETAIL PLATE NO: 8005

APPROVED: ADOPTED BY CITY COUNCIL ON APRIL 13, 2009

**REVISED:** REVISION ADOPTED BY CITY COUNCIL ON AUGUST 8, 2011

**REMARKS:** NOVEMBER 5, 2010 PER MMUTCD 2010

**SAINT** UTILITY STANDARD DETAIL PETER

